

# PlumbingVoid™ System

---

- STANDARD SYSTEM FOR USE IN CONVENTIONAL TRENCHES UP TO 8' IN DEPTH
- SYSTEM HEIGHTS (18" , 24" , 30" , 32" & 36") AND WIDTHS (18" & 24") ALLOW LARGER OR MULTIPLE PIPES TO BE Laterally SUSPENDED TOGETHER
- THE SYSTEM COMPONENTS SHOULD BE ASSEMBLED IN A PROCEDURAL SEQUENCE
- EXCAVATED TRENCHES CAN MATCH THE GENERAL SLOPE OF THE PLUMBING LINES OR DUG IN LEVEL STEPS TO ACHIEVE THE NEEDED ELEVATION(S)
- TRENCH DEPTHS MUST BE DEEP ENOUGH SO THE ENTIRE SYSTEM IS BELOW GRADE ENSURING THE SPECIFIED VOID SPACE REMAINS UNDER THE SLAB
- TRENCH WIDTHS SHOULD BE A MINIMUM OF 6" WIDER THAN THE SIZE OF THE SELECTED SYSTEM FOR NECESSARY ALIGNMENT
- TRENCHES SHOULD BE 6" DEEPER FOR A SUPPORTIVE GRAVEL BASE IF WATER ACCUMULATES IN THE TRENCH
- CLEVIS AND ALL-THREAD IS NOT INCLUDED
- INSTALL PER MANUFACTURE'S RECOMMENDATIONS
- DO NOT DRIVE MACHINERY OVER SYSTEM

