

WallVoid® Technical Notes

WallVoid® contains various corrugated papers of different strengths and flutes, bonded together with white, water-based adhesive or held in place with staples. Its structural strength is designed to weaken by the gradual absorption of moisture as the concrete sets. Thus, an adequate void is attained which will allow the ground to heave into the created space without causing structural damage to the concrete wall or grade beam. The WallVoid interior is composed of mostly biodegradable, cellular network and is surrounded by a wax-coated exterior cover.

TYPES AVAILABLE

- ◆ WallVoid® – for use in conventional forming, it is manufactured with a panel flange on which the concrete form rests, ensuring proper positioning during the concrete pour, and preventing the void piece from floating up into the wall.

ADVANTAGES

1. Lightweight
2. Easy to install
3. Waxed exterior for initial water resistance.
4. Can be sent either assembled or knockdown (K.D.)

AVAILABLE DIMENSIONS

HEIGHT – approximately 4” to 24”
WIDTH – approximately 6” to 30”
LENGTH – approximately 60”

TECHNICAL DATA

COVER –

- a) 275# or 44 ECT, C-flute Corrugated Paper
- b) Waxed / printed exterior
- c) Scored interior

INTERIOR – 200# - 275# or 44 ECT, B or C-flute or DW Corrugated Paper

STRENGTH – Working load as recommended for wall heights of up to 42 feet

RECOMMENDATIONS

1. Keep WallVoid dry at all times prior to concrete placement.
2. Prepare grade to an even, smooth surface.
3. Install ArcVoid® sets or SureRound PierVoid® at piers where required.
4. Place WallVoid pieces end to end in wall line.
5. Crosscut pieces from the bottom side with handsaw to fit into non-modular areas.
6. Insert End Caps on open pieces that will be exposed to concrete.
7. Tape joints, use seam pads or hardboard to prevent immediate water or concrete silt penetration.
8. Install steel.
9. If void piece has a panel flange, place inside form on top of it. This will prevent the piece from floating up into the wall during the pour.
10. Place concrete.